

# Roamer 24-230SMART5

## 25.6V 230AH 300A LIFEPO4

The Roamer 24-240SMART5 is a 24V configuration of the 460SMART5. By increasing the voltage to 24V the current output at any given power draw is halved when compared to 12V batteries, reducing load on copper cabling and transformers. Ideal for systems already operating at 24V. NOTE this battery model cannot be connected in series. Doing so could permanently damage the BMS. For more information, visit [www.roamer.com/products/24-230smart](http://www.roamer.com/products/24-230smart)

### General Description

All Roamer batteries utilise Lithium Iron Phosphate (LFP or LiFePO4) cell chemistry combined with an intelligent, Bluetooth connected Battery Management System (BMS). Roamer only use Grade A cells direct from the manufacturer, matched at the factory to ensure coherent operation and maximise service life and safety. The batteries are constructed around a custom fabricated steel chassis which supports and protects the cells from mechanical impacts and vibration and facilitates high levels of serviceability, ensuring that our batteries can be upgraded or serviced to maximise the service of the product.

Fire retardant materials including fibreglass resin panels and high-density carbon-impregnated EVA foam are used to provide high quality electrical and thermal insulation, and mechanical protection. All batteries are fitted with female M10x1.25 terminals with large contact surface area. All batteries have multi-layered safety features as standard including over and under voltage, over and under temperature for both charge and discharge, short circuit detection, cell balance monitoring and more. High specification components are used to provide passive protection from accidental extreme DC overvoltage, reverse polarity, and momentary overcurrent.





### PRODUCT FEATURES

- 230Ah capacity at 25.6V
- Intelligent cell balancing up to 2A
- Grade A Prismatic LFP cells
- Up to 300A continuous discharge (7.2kW)
- Supports 2 batteries in series and up to 16 parallel for increased capacity, current delivery, voltage, or supply redundancy
- Discharge between -20 °C and 60 °C, charge between 0 °C and 60 °C



## Battery Dimensions

Dimensions subject to manufacturing variation. Products may vary from those illustrated. This drawing is subject to change without notice.



## Battery Specification

	Identifier	Min	Typical	Max	Unit
Nominal Voltage	$V_N$	-	25.6	-	V
Nominal Capacity	$C_N$	-	230	253	Ah
Energy Capacity	$E_N$	-	5888	-	W
Cell Chemistry	-	-	LFP	-	-
Cell Type	-	-	Prismatic	-	-
Cell Capacity	$C_C$	230	230	-	Ah
Cell Configuration	-	-	8S 1P	-	-
Pack Internal Resistance	$R_I$	-	-	20	$m\Omega$
Parallel Limit	$N_P^{MAX}$	-	-	16	-
Series Limit	$N_S^{MAX}$	-	-	NOT ALLOWED	-
Cycle Life at 80% DoD	-	-	8000	-	-

## Physical Specification

	Identifier	Min	Typical	Max	Unit
Length	$L_L$	-	522	-	mm
Width	$L_W$	-	270	-	mm
Depth	$L_D$	-	228	-	mm
Mass	$M$	-	38	-	kg
Case Type	-	-	ABS Serviceable	-	-
Terminal Type	-	-	M10 Female	-	-
Terminal Torque Rating	$T_{MAX}$	15	16	17	Nm
IP Rating	-	-	IP54	-	-

## Charging Parameters

	Identifier	Min	Recommended	Max	Unit
Battery Safe Voltage	$V_{BS}$	20	-	29.2	V
Battery Working Voltage	$V_{BW}$	21.6	-	28.8	V
Nominal Cell Voltage	$V_{CN}$	2.8	-	3.7	V
Absorption Voltage	$V_{CA}$	-	28.4	29.2	V
Float Voltage	$V_{CF}$	-	27	-	V
Maintenance Voltage	$V_{CS}$	-	26.5	-	V
BMS Charge Current Limit	$I_c$	5	-	230	A
Recommended Max Charge Rate	$R_c$	-	-	115	A
Charge Temperature	$T_c$	0	-	60	°C
Charge Current >25°C	$I_{CMAX}^{25}$	-	-	115	A
Charge Current @ 10°C	$I_{CMAX}^{10}$	-	-	46	A
Charge Current @ 5°C	$I_{CMAX}^5$	-	-	23	A
Charge Current < 0°C	$I_{CMAX}^0$	-	-	0	A
Charge Current < -20°C	$I_{CMAX}^{-20}$	-	-	0	A

## Discharging Parameters

	Identifier	Min	Recommended	Max	Unit
BMS Peak Discharge Current (30s)	$I_{CP}$	0	-	450	A
BMS Max Continuous Discharge Current	$I_{CC}$	0	-	300	A
Recommended Max Discharge Rate	$R_d$	-	-	230	A
Discharge Temperature	$T_d$	-20	-	60	°C

## Storage Parameters







	Identifier	Min	Recommended	Max	Unit
Recommended Storage Temperature	$T_s$	10	-	35	°C
Recommended Storage SoC	$S_s$	30	50	80	%
Recommended Storage Voltage	$V_s$	26	26.5	26.7	V

## BMS Parameters

	Identifier	Min	Typical	Max	Unit
Cell Overcharge Detection Voltage	$V_{COD}$	-	3.65	-	V
Cell Overcharge Release Voltage	$V_{COR}$	-	3.4	-	V
Pack Overcharge Detection Current	$I_{BOD}$	-	300	-	A
Pack Overcharge Release Current	$I_{BOR}$	-	0	-	A
Overcharge Detection Time	$t_{OD}$	-	1	-	s
Cell Undercharge Detection Voltage	$V_{CUD}$	-	2.5	-	V
Cell Undercharge Release Voltage	$V_{CUR}$	-	2.7	-	V
Undercharge Detection Time	$t_{UD}$	-	1	-	s
Cell Balance Transfer Current	$I_{CB}$	-	2	-	A
Cell Balance Trigger Delta Threshold Voltage	$V_{CBD}$	-	0.01	-	V
Short Circuit Detection Current	$I_{SCD}$	-	2200	-	A
Short Circuit Protection Release Current	$I_{SCR}$	-	5	-	A
Short Circuit Detection Time	$t_{SC}$	-	150	200	$\mu$ s
Charge Temperature Protection	$T_{CPD}$	0	-	60	$^{\circ}$ C
Charge Temperature Protection Release	$T_{CPR}$	5	-	55	$^{\circ}$ C
Discharge Temperature Protection	$T_{DP}$	-20	-	60	$^{\circ}$ C
Discharge Temperature Protection Release	$T_{DPR}$	-15	-	55	$^{\circ}$ C
BMS Working Current Consumption	$I_{WRK}$	-	30	-	mA
BMS Standby Current Consumption	$I_{STBY}$	-	800	-	$\mu$ A

## Battery Characteristics

The following graphs demonstrate the operational characteristics of LiFePo4 cells under a variety of conditions. Many factors play a role in the exact capacity, performance, lifetime and safety of a lithium battery so every installation varies depending on the exact setup and use case. These serve only as a guide and do not reflect the exact characteristics of any individual battery.



## Document Information

Document Version	Release Date	Status	Change Notice
1.0	11/12/2022	Release	Initial issue
2.0	16/08/2023	Release	Major revision
3.0	13/05/2024	Release	Major revision
4.0	13/10/2025	Release	Major revision
4.1	13/02/2026	Release	Change to recommended abs voltage and added comments about series

All efforts have been made to ensure the data in this datasheet are correct and up to date. Roamer Batteries constantly monitor product documentation for inaccuracy and routinely update documentation to reflect the most accurate information available. This version of the document supersedes and replaces all information supplied prior to the publication hereof.

Roamer reserves the right to change the contents of this document without prior notice. Roamer, the Roamer Logo, and any other marks are trademarks of Roamer Batteries Ltd. or its subsidiaries. For more information, see Roamer.com. Other names and brands may be claimed as the property of others. ©2024 Roamer Batteries Ltd. All rights reserved. Products may vary slightly from those pictured.